

## Quality

### MTPXATY1000-PU

Fabric Weight	350gsm +/- 5%
Composition	1000d x 1000d (13 x 11/cm) Polyester Oxford
Finish	PU-Coated, Water-Resistant
Useable Width	150cm
Application	Workwear

#### Physical Properties

	Warp	Weft
Tensile Strength (BS EN ISO 13934-1:2013)	2500 N	2400 N
Tear Strength (BS EN ISO 4674-1:2016)	>200N	>200 N

	As Received	After 5 Washes
Abrasion Resistance (BS EN ISO 12947-2:2016)	NA	NA
Dimensional Stability (BS EN ISO 6330)	<3%	NA
Spray Rating (BS EN ISO 4920:2012)	5	NA
Water Vapour Resistance RET (BS EN ISO 11092)	NA	NA
Resistance to Water Penetration (BS EN ISO 20811)	1000mm	1000mm
<b>Colour Fastness</b>		
Light Fastness (BS EN ISO 105-E16:2006)	>4	
Colour Fastness to Water (BS EN ISO 105-E01:2013)	>4	
Perspiration Fastness Acid/Alkaline (BS EN ISO 105-E04)	>4	
Wash Fastness (BS EN ISO 105-C10:2006) 40 Degrees	>4	
Rub Fastness Wet/Dry (BS EN ISO 105-X12:1995)	>4	

#### Other Properties

Hi-Visibility	
BS EN ISO 20471:2013 Yellow and Orange	PASS

The information contained in this product datasheet is based on results obtained from the sample assessed, following the method provided. The values are a guide for purchasers of the fabric to evaluate and determine its suitability for their product's intended end use.